Safety Data Sheet



Revision Number: 002.0

Issue date: 04/05/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

Product type: Assen Restriction of Use: None Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

PL 530 Mirror, Marble & Granite Construction Adhesive Assembly adhesive, solvent None identified

IDH number:

1693636

Region:United StatesContact information:Telephone: +1 (800) 624-7767MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCYPhone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW			
ABRASION COULD RELEASE RESPIRABLE PARTICLES OF SILICA QUARTZ,			
A CANCER HAZARD BY INHALATION. NORMAL USE OF THIS PRODUCT			
CAUSES NO SUCH RELEASE.			
HIGHLY FLAMMABLE LIQUID AND VAPOR.			
CAUSES SERIOUS EYE IRRITATION.			

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
EYE IRRITATION	2A

PICTOGRAM(S)	

Precautionary Statements

Prevention:	
	Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face protection.
Response:	
	If on skin (or hair): Take off immediately all contaminated clothing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.
Storage:	v
	Store in a well-ventilated place. Keep cool.
Disposal:	
	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Limestone	1317-65-3	10 - 30	
Kaolin	1332-58-7	10 - 30	
Acetone	67-64-1	10 - 30	
Rosin ester	Proprietary	1 - 5	
Methyl acetate	79-20-9	1 - 5	
Titanium dioxide	13463-67-7	0.1 - 1	
Quartz (SiO2)	14808-60-7	0.1 - 1	

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES			
Inhalation:	If inhaled, immediately remove the affected person to fresh air. If breathing i difficult, give oxygen. If symptoms develop and persist, get medical attentior		
Skin contact:	Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention.		
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 18 minutes, and seek immediate medical attention.		
Ingestion:	Do not induce vomiting, seek medical advice immediately.		
Symptoms:	See Section 11.		
Notes to physician:	Treat symptomatically and supportively.		
5. F	IRE FIGHTING MEASURES		
Extinguishing media:	Foam, dry chemical or carbon dioxide. In case of fire, keep containers cool with water spray.		
Special firefighting procedures:	Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode. Wear full protective clothing.		
Unusual fire or explosion hazards:	Closed containers may explode when exposed to extreme heat. Vapors ma form explosive mixtures with air. Vapors are heavier than air and may trave along floor to an ignition source.		

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Eliminate all sources of ignition or flammables that may come into contact with a spill of this material. Ventilate area. Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways. **Clean-up methods:**

Use noncombustible absorbent material such as sand. Use non-sparking tools for clean-up. Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling:

Do not pressurize, cut, heat or weld containers. Empty product containers may contain product residue. Do not reuse empty containers. Use only in well-ventilated areas. Keep out of the reach of children. Keep away from heat, spark and flame. Containers should be grounded and bonded to the receiving container.

Storage:

For safe storage, store between -20 °C (-4°F) and 50 °C (122°F) Keep away from heat, spark and flame. Keep containers closed when not in use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Kaolin	2 mg/m3 TWA Respirable fraction.	15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction.	None	None
Acetone	250 ppm TWA 500 ppm STEL	1,000 ppm (2,400 mg/m3) PEL	None	None
Rosin ester	None	None	None	None
Methyl acetate	200 ppm TWA 250 ppm STEL	200 ppm (610 mg/m3) PEL	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 PEL Total dust.	None	None
Quartz (SiO2)	0.025 mg/m3 TWA Respirable fraction.	0.3 mg/m3 TWA Total dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None
Engineering controls:		xhaust ventilation is reco nt to control airborne con		

Respiratory protection:

Eye/face protection:

Skin protection:

limits.

Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists. When workplace hazards warrant the use of a respirator, appropriate respirators must be used, and a program that follows 29 CFR 1910.134 must be followed.

Safety goggles or safety glasses with side shields.

Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid or paste
Color:	Beige
Odor:	Acetone-like
Odor threshold:	Not available.
pH:	7
Vapor pressure:	Not available.
Boiling point/range:	56 - 57 °C (132.8 - 134.6 °F)
Melting point/ range:	< 0 °C (< 32°F)
Specific gravity:	1.44
Vapor density:	2.0
Flash point:	-17 °C (1.4 °F)
Flammable/Explosive limits - low	
Flammable/Explosive limits - upp	
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	14.4
Solubility in water:	Slightly soluble
Partition coefficient (n-octanol/wa	
VOC content:	0.22 %; 5.67 g/l (by weight, calculated using CARB method; g/L less water,
VOO coment.	less exempts calculated using SCAQMD method)
Viscosity:	375.000 mPa.s
Decomposition temperature:	Not available.
Decomposition temperature.	NUL AVAIIADIE.
	10. STABILITY AND REACTIVITY
a	
Stability:	Stable under normal conditions of storage and use.

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.
Incompatible materials:	Strong oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Heat, flames, sparks and other sources of ignition.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Inhalation, Skin contact

Potential Health Effects/Symptoms

Inhalation:	Irritates the nose, throat and respiratory system. Exposure to high doses may cause central nervous system depression. Such doses may also cause adverse effects in the liver, kidneys, and lungs. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
Skin contact:	Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.
Eye contact:	Contact with eyes can cause eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Ingestion:	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Limestone	None	Nuisance dust	
Kaolin	Oral LD50 (Rat) = > 5,000 mg/kg Nuisance dust Dermal LD50 (Rat) = > 5,000 mg/kg Nuisance dust		
Acetone	Oral LD50 (Mouse) = 3,000 mg/kg Oral LD50 (Rabbit) = 5,340 mg/kg Oral LD50 (Rat) = 5,800 mg/kg Oral LD50 (Rat) = 9,800 mg/kg Oral LD50 (Mouse) = 5.2 g/kg Dermal LD50 (Rabbit) = 20,000 mg/kg Inhalation LC50 (Rat, 4 h) = 76 mg/l	Central nervous system, Irritant	
Rosin ester	None	Irritant	
Methyl acetate	Oral LD50 (Rabbit) = 3.7 g/kg	Blood, Central nervous system, Eyes, Irritant	
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity	
Quartz (SiO2)	None	Immune system, Lung, Some evidence of carcinogenicity	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Kaolin	No	No	No
Acetone	No	No	No
Rosin ester	No	No	No
Methyl acetate	No	No	No
Titanium dioxide	No	Group 2B	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	No

12. ECOLOGICAL INFORMATION

Ecological information:

None expected.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according t	o Federal, State and local governmental regulations.
--	--

Hazardous waste number:

It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24. If discarded, this product is considered a RCRA ignitable waste, D001.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)	
Proper shipping name:	Adhesives
Hazard class or division:	3
Identification number:	UN 1133
Packing group:	II
International Air Transportation (ICAO/IATA)	
Proper shipping name:	Adhesives
Hazard class or division:	3
Identification number:	UN 1133
Packing group:	II
Water Transportation (IMO/IMDG)	
Proper shipping name:	ADHESIVES
Hazard class or division:	3
Identification number:	UN 1133
Packing group:	II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Fire, Immediate Health, Delayed Health None above reporting de minimis.
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2, 3, 8, 11, 15

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

Issue date: 04/05/2016

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.