



ALL PURPOSE

3006™ ADVANCED FORMULA

Siliconized Acrylic Latex Caulk



White Lightning® 3006™ Advanced Formula provides a smooth application that can be painted in 30 minutes! It is ideal for filling joints and openings around doors, windows, baseboards, trim, siding and vents. For use on: wood, drywall, metal, glass, masonry and most plastics.

- Smooth Application
- Excellent Adhesion to Most Surfaces
- Cured Sealant is Mold and Mildew Resistant
- Paintable in 30 minutes



PAINTABLE



INTERIOR/
EXTERIOR



WATER
CLEANUP



PART #	UPC	Color	SIZE
W12AF0010	0-23275-30060-6	White	10 fl oz
W12AF0005	0-23275-30066-8	White	5.5 fl oz

WHITE



ALL PURPOSE

3006
ADVANCED
FORMULA™

Smooth
Application

- Excellent Adhesion to Most Surfaces
- Cured Caulk is Mold and Mildew Resistant
- Paintable in 30 minutes

SILICONIZED
ACRYLIC
LATEX CAULK



PAINTABLE



INTERIOR/
EXTERIOR



WATER CLEANUP

Exceeds
ASTM C-834





**WHITE
LIGHTNING®**

**ALL PURPOSE
3006™ ADVANCED FORMULA**

Product Description:

White Lightning® 3006™ Advanced Formula provides a smooth application that can be painted in 30 minutes! It is ideal for filling joints and openings around doors, windows, baseboards, trim, siding and vents. For use on: wood, drywall, metal, glass, masonry and most plastics.

Physical Properties:

Type: 100% Pure Acrylic With Silicone

Colors: White

Shelf Life: 24 Months

Flash Point: n/a (water based)

Flammability: n/a (water based)

Full Cure Time: 5 to 7 days at 75° F

Tack Free Time: 10 Minutes

Application Temperature: above 40° F

Service Temperature: -30° F to 180° F

Vehicle: Premium siliconized acrylic polymer

Solids by Weight: 83.5 ± 1%

Weight/Gallon: 13.2 ± 0.2 lb

Painting: Paintable

Primers: Not required

Mildew Resistance: Cured caulk resists mildew growth

Water Resistance: Good

Odor: Low

Shrinkage: Low/Moderate

Performance Data:

Joint Size: 1/8" x 1/8" to 1/2" x 1/2"

Freeze-Thaw Stability: Stable through 5 Cycles

Shelf Life: 24 Months

Clean Up: Clean tools and excess sealant with soap and water or a damp cloth while still wet.

Flexibility: Very Good

Linear Coverage 10oz cartridge 24ft at 1/4" wide by 1/4" deep bead; 5.5oz squeeze tube 12ft at 1/4" wide by 1/4" deep bead

Painting: (Temperature and Humidity Dependent) Can be painted with latex or oil based paint after 30 minutes dry time at 75°F and 50% relative humidity. Allow extra dry time during periods of high humidity and/or cool temperatures.

ASTM: Exceeds ASTM C-834

**White Lightning® 3006™ Advanced Formula
has achieved GREENGUARD GOLD Certification.**

For more information please call or write:

Application:

1. Remove all existing caulk
2. Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
3. Remove mold/mildew with bleach (4:1 mix, water to bleach), and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

• 10oz cartridge

- Cut cartridge tip 45° angle.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

• 5.5oz cartridge

- Remove cap, cut tube tip 45° angle.
- Squeeze tube to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

Clean Up:

Water, promptly clean tools and excess sealant with water or a damp cloth while still wet.

Cautions:

See SDS

Limitations:

For best results, apply at temperatures above 40° F and allow 24 hours to cure before exposing to moisture. Do not apply to frozen or frost covered surfaces. Not for use below grade, on aquariums or for marine use below the water line

LIMITED WARRANTY:

If when applied according to label directions within one year from date of purchase this product fails to perform to your satisfaction, as your sole remedy we will replace the product at no cost or refund the original purchase price with proof of purchase. Labor or costs associated with labor not included. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.

White Lightning® Products | 101 Prospect Ave. NW | Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service | 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com

3006™ ADVANCED FORMULA