

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: FlintPrime QD

Product Code: 410

Intended Use of the Product

Roofing/Waterproofing

Name, Address, and Telephone of the Responsible Party

Company

Saint Gobain CertainTeed
20 Moores Road
Malvern, PA 19355
Professional: 800-233-8990
Consumer: 800-782-8777

www.certainteed.com

Emergency Telephone Number

Emergency Number :

Chemtel

Domestic: 1-800-255-3924

International: +1-813-248-0585

Australia: 1-300-954-583

Brazil: 0-800-591-6042

China: 400-120-0751

India: 000-800-100-4086

Mexico: 800-099-0731

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Carc. 2	H351
STOT SE 3	H336
Aquatic Acute 2	H401
Aquatic Chronic 2	H411

Full text of hazard classes and H-statements : see section 16

Label Elements

GHS Labeling

Hazard Pictograms



Signal Word

: Warning

Hazard Statements

: H226 - Flammable liquid and vapor.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H351 - Suspected of causing cancer.
H401 - Toxic to aquatic life.
H411 - Toxic to aquatic life with long lasting effects.

FlintPrime QD

Safety Data Sheet

According to U.S. Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations and according to Canada's Hazardous Products Regulation, February 11, 2015.

Precautionary Statements

- : P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 - Keep container tightly closed.
- P240 - Ground/bond container and receiving equipment.
- P241 - Use explosion-proof electrical, ventilating, and lighting equipment.
- P242 - Use only non-sparking tools.
- P243 - Take action to prevent static discharges.
- P261 - Avoid breathing dust, fume, vapors.
- P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.
- P273 - Avoid release to the environment.
- P280 - Wear protective gloves, protective clothing, and eye protection.
- P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
- P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 - If exposed or concerned: Get medical advice/attention.
- P312 - Call a POISON CENTER or doctor if you feel unwell.
- P321 - Specific treatment (see section 4 on this SDS).
- P332+P313 - If skin irritation occurs: Get medical advice/attention.
- P337+P313 - If eye irritation persists: Get medical advice/attention.
- P362+P364 - Take off contaminated clothing and wash it before reuse.
- P370+P378 - In case of fire: Use carbon dioxide (CO₂), dry sand, extinguishing powder, foam to extinguish.
- P391 - Collect spillage.
- P403+P235 - Store in a well-ventilated place. Keep cool.
- P405 - Store locked up.
- P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

Unknown acute toxicity

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Synonyms	Product Identifier	%*	GHS Ingredient Classification
Asphalt	Asphalt (petroleum) / Bitumens	(CAS-No.) 8052-42-4	50 – 80	Carc. 2, H351
Stoddard solvent	Turpentine, mineral / White spirits	(CAS-No.) 8052-41-3	20 – 25	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Naphtha, petroleum, heavy alkylate	Naphtha (petroleum), heavy alkylate / Ligroine (petroleum), heavy alkylate	(CAS-No.) 64741-65-7	18 – 25	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

FlintPrime QD

Safety Data Sheet

According to U.S. Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations and according to Canada's Hazardous Products Regulation, February 11, 2015.

Naphtha, petroleum, hydrotreated heavy	Naphtha (petroleum), hydrotreated heavy / Aliphatic oil	(CAS-No.) 64742-48-9	18 – 25	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Solvent naphtha, petroleum, light aromatic	Solvent naphtha (petroleum), light aromatic	(CAS-No.) 64742-95-6	5 – 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Benzene, 1,2,4-trimethyl-	Pseudocumene / 1,2,4-Trimethylbenzene	(CAS-No.) 95-63-6	≤ 1.35	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapor), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Nonane	n-Nonane / NONANE	(CAS-No.) 111-84-2	≤ 1	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapor), H332 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

**Product contains CAS 8052-41-3 OR CAS 64741-65-7 OR CAS 64742-48-9.

SECTION 4: FIRST AID MEASURES

Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Immediately remove contaminated clothing. Immediately drench affected area with water for at least 15 minutes. If exposed or concerned: Get medical advice/attention.

Eye Contact: Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes skin irritation. May cause drowsiness and dizziness. Causes serious eye irritation. Suspected of causing cancer.

Inhalation: High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: Suspected of causing cancer.

FlintPrime QD

Safety Data Sheet

According to U.S. Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations and according to Canada's Hazardous Products Regulation, February 11, 2015.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Carbon dioxide, foam, sand, dry chemical powder. Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: May form flammable or explosive vapor-air mixture.

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Hydrocarbons.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe vapor, mist or spray. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Eliminate ignition sources first, then ventilate the area.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Use only non-sparking tools. Clean up spills immediately and dispose of waste safely. Do not take up in combustible material such as: saw dust or cellulosic material. Absorb and/or contain spill with inert material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not breathe dust, fume, gas, vapors. Take precautionary measures against static discharge. Use only non-sparking tools. Do not get in eyes, on skin, or on clothing.

Handling Temperature: < 110 °F

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

FlintPrime QD

Safety Data Sheet

According to U.S. Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations and according to Canada's Hazardous Products Regulation, February 11, 2015.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Storage Temperature: < 110 °F

Specific End Use(s)

Roofing/Waterproofing

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters


For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Asphalt (8052-42-4)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.5 mg/m ³ (fume, inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen fume, coal tar-free
USA ACGIH	Biological Exposure Indices (BEI)	2.5 µg/l Parameter: 1-Hydroxypyrene with hydrolysis - Medium: urine - Sampling time: end of shift at end of workweek (background) Parameter: 3-Hydroxybenzo(a)pyrene with hydrolysis - Medium: urine - Sampling time: end of shift at end of workweek (nonquantitative)
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	5 mg/m ³ (fume)
Stoddard solvent (8052-41-3)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2900 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	350 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	1800 mg/m ³
USA IDLH	US IDLH (mg/m ³)	20000 mg/m ³
Benzene, 1,2,4-trimethyl- (95-63-6)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	125 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	25 ppm
Nonane (111-84-2)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1050 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	200 ppm

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.

Hand Protection: Wear protective gloves.

Eye Protection: Chemical safety goggles.

FlintPrime QD

Safety Data Sheet

According to U.S. Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations and according to Canada's Hazardous Products Regulation, February 11, 2015.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Black fibered mastic
Odor	: Petroleum-like
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: > 300 °F (148.89 °C)
Flash Point	: 106 °F (41.11 °C)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not applicable
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: 0.293 kPa at 20 °C
Relative Vapor Density at 20°C	: Not available
Relative Density	: 1.02 – 1.12
Density	: 8.5 – 9.3 lb/gal
Specific Gravity	: Not available
Solubility	: Water: 0 % Organic solvent: ≈100 %
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Viscosity, Kinematic	: > 20.5 mm ² /s at 40 °C
VOC content	: ≤ 250 g/l

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

Chemical Stability: Flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Hazardous Decomposition Products: Thermal decomposition may produce: Carbon oxides (CO, CO₂). Hydrocarbons.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation.

Eye Damage/Irritation: Causes serious eye irritation.

FlintPrime QD

Safety Data Sheet

According to U.S. Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations and according to Canada's Hazardous Products Regulation, February 11, 2015.

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Suspected of causing cancer.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness or dizziness.

Aspiration Hazard: Not classified

Symptoms/Effects After Inhalation: High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Symptoms/Effects After Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Effects After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Effects After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: Suspected of causing cancer.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Asphalt (8052-42-4)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 94.4 mg/m ³
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
LD50 Oral Rat	8400 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	3400 ppm/4h
Stoddard solvent (8052-41-3)	
LD50 Oral Rat	> 5 g/kg Behavioral somnolence
LD50 Dermal Rabbit	> 3 g/kg
LC50 Inhalation Rat	> 5500 mg/l/4h Behavioral somnolence
Naphtha, petroleum, heavy alkylate (64741-65-7)	
LD50 Oral Rat	> 7000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 5.04 mg/l/4h
Naphtha, petroleum, hydrotreated heavy (64742-48-9)	
LD50 Oral Rat	> 6000 mg/kg
LD50 Dermal Rabbit	> 3160 mg/kg
LC50 Inhalation Rat	> 8500 mg/m ³ (Exposure time: 4 h)
Benzene, 1,2,4-trimethyl- (95-63-6)	
LD50 Oral Rat	6000 mg/kg
LD50 Dermal Rabbit	> 3160 mg/kg
LC50 Inhalation Rat	18 g/m ³ (Exposure time: 4 h)
LC50 Inhalation Rat	10.8 mg/l/4h
Nonane (111-84-2)	
LC50 Inhalation Rat	16.75 mg/l/4h
LC50 Inhalation Rat	3200 ppm/4h
Asphalt (8052-42-4)	
IARC Group	2A, 2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Toxic to aquatic life with long lasting effects.

Solvent naphtha, petroleum, light aromatic (64742-95-6)

FlintPrime QD

Safety Data Sheet

According to U.S. Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations and according to Canada's Hazardous Products Regulation, February 11, 2015.

LC50 Fish 1	9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Stoddard solvent (8052-41-3)	
EC50 Daphnia 1	0.42 mg/l
NOEC Chronic Algae	0.16 mg/l
Naphtha, petroleum, heavy alkylate (64741-65-7)	
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Mysidopsis bahia)
Naphtha, petroleum, hydrotreated heavy (64742-48-9)	
LC50 Fish 1	2200 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
Benzene, 1,2,4-trimethyl- (95-63-6)	
LC50 Fish 1	7.19 (7.19 – 8.28) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Nonane (111-84-2)	
EC50 Daphnia 1	0.2 mg/l

Persistence and Degradability

FlintPrime	
Persistence and Degradability	Not expected to be readily biodegradable. May cause long-term adverse effects in the environment.

Bioaccumulative Potential

FlintPrime	
Bioaccumulative Potential	Not established.
Asphalt (8052-42-4)	
BCF Fish 1	(no bioaccumulation expected)
Partition coefficient n-octanol/water (Log Pow)	> 6
Stoddard solvent (8052-41-3)	
Partition coefficient n-octanol/water (Log Pow)	3.16 (Octanol/water partition coefficient 3.16/7.06)
Benzene, 1,2,4-trimethyl- (95-63-6)	
Partition coefficient n-octanol/water (Log Pow)	3.63

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

*When shipped in accordance with US DOT 49 CFR part 171.4(c) and other appropriate sections/provisions this material is not designated as a marine pollutant when transported by road or rail.





**When shipped in accordance with the Canada Transport of Dangerous Goods Regulations part 1.45.1 and other appropriate sections/provisions this material is not designated as a marine pollutant when transported by road or rail

TRANSPORTATION CLASSIFICATION	DOT	TDG	IMDG	IATA

FlintPrime QD

Safety Data Sheet

According to U.S. Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations and according to Canada's Hazardous Products Regulation, February 11, 2015.

Identification Number	UN1268	UN1268	UN1268	UN1268
Proper Shipping Name	PETROLEUM PRODUCTS, N.O.S	PETROLEUM PRODUCTS, N.O.S.	PETROLEUM PRODUCTS, N.O.S.	PETROLEUM DISTILLATES, N.O.S.
Transport Hazard Class(es)	3	3	3	3
				
Packing Group	III	III	III	III
Environmental Hazards	Marine Pollutant : Yes*	Marine Pollutant : Yes**	Marine Pollutant : Yes	Marine Pollutant: N/A
Emergency Response	ERG Number : 128	ERAP Index: Not applicable	EMS: F-E, S-E	ERG code (IATA): 3L
Additional Information	Not applicable	Not applicable	Not applicable	Not applicable

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Chemical Name (CAS No.)	CERCLA RQ	EPCRA 304 RQ	SARA 302 TPQ	SARA 313
Asphalt (8052-42-4)	Not applicable	Not applicable	Not applicable	No
Solvent naphtha, petroleum, light aromatic (64742-95-6)	Not applicable	Not applicable	Not applicable	No
Stoddard solvent (8052-41-3)	Not applicable	Not applicable	Not applicable	No
Naphtha, petroleum, heavy alkylate (64741-65-7)	Not applicable	Not applicable	Not applicable	No
Naphtha, petroleum, hydrotreated heavy (64742-48-9)	Not applicable	Not applicable	Not applicable	No
Benzene, 1,2,4-trimethyl- (95-63-6)	Not applicable	Not applicable	Not applicable	Yes
Nonane (111-84-2)	Not applicable	Not applicable	Not applicable	No

SARA 311/312

FlintPrime


Health hazard - Carcinogenicity. Health hazard - Specific target organ toxicity (single or repeated exposure). Health hazard - Skin corrosion or Irritation. Physical hazard - Flammable (gases, aerosols, liquids, or solids). Health hazard - Serious eye damage or eye irritation

US TSCA Flags

Chemical Name (CAS No.)	US TSCA Flags/ Other Information
Nonane (111-84-2)	T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.

US State Regulations

California Proposition 65

 **WARNING:** This product can expose you to Asphalt, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Asphalt (8052-42-4)	Yes	No	No	No
Solvent naphtha, petroleum, light aromatic (64742-95-6)	No	No	No	No
Stoddard solvent (8052-41-3)	No	No	No	No
Naphtha, petroleum, heavy alkylate (64741-65-7)	No	No	No	No
Naphtha, petroleum, hydrotreated heavy (64742-48-9)	No	No	No	No

FlintPrime QD

Safety Data Sheet

According to U.S. Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations and according to Canada's Hazardous Products Regulation, February 11, 2015.

9)				
Benzene, 1,2,4-trimethyl- (95-63-6)	No	No	No	No
Nonane (111-84-2)	No	No	No	No

State Right-To-Know Lists

Asphalt (8052-42-4)

U.S. - Massachusetts - Right To Know List - Yes
U.S. - New Jersey - Right to Know Hazardous Substance List - Yes
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List - No
U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances - No
U.S. - Pennsylvania - RTK (Right to Know) List - Yes

Solvent naphtha, petroleum, light aromatic (64742-95-6)

U.S. - Massachusetts - Right To Know List - No
U.S. - New Jersey - Right to Know Hazardous Substance List - No
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List - No
U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances - No
U.S. - Pennsylvania - RTK (Right to Know) List - No

Stoddard solvent (8052-41-3)

U.S. - Massachusetts - Right To Know List - Yes
U.S. - New Jersey - Right to Know Hazardous Substance List - Yes
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List - No
U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances - No
U.S. - Pennsylvania - RTK (Right to Know) List - Yes

Naphtha, petroleum, heavy alkylate (64741-65-7)

U.S. - Massachusetts - Right To Know List - No
U.S. - New Jersey - Right to Know Hazardous Substance List - No
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List - No
U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances - No
U.S. - Pennsylvania - RTK (Right to Know) List - No

Naphtha, petroleum, hydrotreated heavy (64742-48-9)

U.S. - Massachusetts - Right To Know List - No
U.S. - New Jersey - Right to Know Hazardous Substance List - No
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List - No
U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances - No
U.S. - Pennsylvania - RTK (Right to Know) List - No

Benzene, 1,2,4-trimethyl- (95-63-6)

U.S. - Massachusetts - Right To Know List - Yes
U.S. - New Jersey - Right to Know Hazardous Substance List - Yes
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List - Yes
U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances - No
U.S. - Pennsylvania - RTK (Right to Know) List - Yes

Nonane (111-84-2)

U.S. - Massachusetts - Right To Know List - Yes
U.S. - New Jersey - Right to Know Hazardous Substance List - Yes
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List - No
U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances - No
U.S. - Pennsylvania - RTK (Right to Know) List - Yes

Canadian Regulations

Asphalt (8052-42-4)

Listed on the Canadian DSL (Domestic Substances List)
Not listed on the Canadian NDSL (Non-Domestic Substances List)

FlintPrime QD

Safety Data Sheet

According to U.S. Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations and according to Canada's Hazardous Products Regulation, February 11, 2015.

Solvent naphtha, petroleum, light aromatic (64742-95-6)
Listed on the Canadian DSL (Domestic Substances List)
Not listed on the Canadian NDSL (Non-Domestic Substances List)
Stoddard solvent (8052-41-3)
Listed on the Canadian DSL (Domestic Substances List)
Not listed on the Canadian NDSL (Non-Domestic Substances List)
Naphtha, petroleum, heavy alkylate (64741-65-7)
Listed on the Canadian DSL (Domestic Substances List)
Not listed on the Canadian NDSL (Non-Domestic Substances List)
Naphtha, petroleum, hydrotreated heavy (64742-48-9)
Listed on the Canadian DSL (Domestic Substances List)
Not listed on the Canadian NDSL (Non-Domestic Substances List)
Benzene, 1,2,4-trimethyl- (95-63-6)
Listed on the Canadian DSL (Domestic Substances List)
Not listed on the Canadian NDSL (Non-Domestic Substances List)
Nonane (111-84-2)
Listed on the Canadian DSL (Domestic Substances List)
Not listed on the Canadian NDSL (Non-Domestic Substances List)

International Inventories/Lists

Chemical Name (CAS No.)	Australia AICS	Turkey CICR	Korea ECL	EU EINECS	EU ELINCS	EU SVHC	EU NLP	Mexico INSQ
Asphalt (8052-42-4)	Yes	No	Yes	Yes	No	No	No	Yes
Solvent naphtha, petroleum, light aromatic (64742-95-6)	Yes	No	Yes	Yes	No	No	No	Yes
Stoddard solvent (8052-41-3)	Yes	No	Yes	Yes	No	No	No	Yes
Naphtha, petroleum, heavy alkylate (64741-65-7)	Yes	No	Yes	Yes	No	No	No	Yes
Naphtha, petroleum, hydrotreated heavy (64742-48-9)	Yes	No	Yes	Yes	No	No	No	Yes
Benzene, 1,2,4-trimethyl- (95-63-6)	Yes	No	Yes	Yes	No	No	No	Yes
Nonane (111-84-2)	Yes	No	Yes	Yes	No	No	No	Yes

Chemical Name (CAS No.)	China IECSC	Japan ENCS	Japan ISHL	Japan PDSCL	Japan PRTR	Philippines PICCS	New Zealand NZIOC	US TSCA
Asphalt (8052-42-4)	Yes	Yes	Yes	No	No	Yes	Yes	Yes
Solvent naphtha, petroleum, light aromatic (64742-95-6)	Yes	No	No	No	No	Yes	Yes	Yes
Stoddard solvent (8052-41-3)	Yes	No	No	No	No	Yes	Yes	Yes
Naphtha, petroleum, heavy alkylate (64741-65-7)	Yes	No	No	No	No	Yes	Yes	Yes
Naphtha, petroleum, hydrotreated heavy (64742-48-9)	Yes	No	No	No	No	Yes	Yes	Yes
Benzene, 1,2,4-trimethyl- (95-63-6)	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes
Nonane (111-84-2)	Yes	Yes	Yes	No	No	Yes	Yes	Yes

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 01/12/2021

FlintPrime QD

Safety Data Sheet

According to U.S. Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations and according to Canada's Hazardous Products Regulation, February 11, 2015.

Revision Summary

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

Acute Tox. 4 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

Abbreviations and Acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

AIHA: American Industrial Hygiene Association

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NIOSH - National Institute for Occupational Safety and Health

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

OEL: Occupational Exposure Limits

PEL: Permissible Exposure Limits

STEL: Short Term Exposure Limit

TLV: Threshold Limit Value

TSCA: United States Toxic Substances Control Act

FlintPrime QD

Safety Data Sheet

According to U.S. Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations and according to Canada's Hazardous Products Regulation, February 11, 2015.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Saint-Gobain NA GHS SDS