



Safety Data Sheet – Gorilla Construction Adhesive

Date Revised:
Date Issued: 3/13/2018

Version: 1.0

FOR CHEMICAL EMERGENCY:
During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: IDENTIFICATION

Product Identifier

Product Name: Gorilla Construction Adhesive

Synonyms: None

Intended Use of the Product

Construction Adhesive

Name, Address, and Telephone of the Responsible Party

Company

The Gorilla Glue Company
2101 E. Kemper Road
Cincinnati, Ohio 45241
513-271-3300

www.gorillatough.com

Emergency Telephone Number

Emergency number : 1-800-420-7186 (Prosar)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US) Not Classified

Label Elements

GHS-US Labeling No labeling applicable

Other Hazards

Other Hazards: Not available

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)
Limestone	(CAS No) 1317-65-3	10-30
Quartz*	(CAS No) 14808-60-7	0.1 - 1

*Finely divided Quartz has caused cancer of the respiratory tract and lung disease in workers that inhaled it over an extended period of time. Studies suggest, however, that these hazards are not associated with other routes of exposure. The quartz in this formulation is in an adhesive matrix and is not expected to be "inhalable." Therefore, these hazards are not expected to be present.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Skin Contact: Wash off immediately with plenty of water for at least 15 minutes. In the case of skin irritation or allergic reactions see a physician.

Eye Contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Do not rub affected area. If eye irritation persists: Get medical advice/attention.

Ingestion: Rinse mouth. Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice. If symptoms persist, call a physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: None known.

Inhalation: None known.

Skin Contact: None known.



Safety Data Sheet – Gorilla Construction Adhesive

Date Revised:
Date Issued: 3/13/2018

Version: 1.0

FOR CHEMICAL EMERGENCY:
During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye Contact: None known.

Ingestion: None known.

Chronic Symptoms: None known.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray (fog). Carbon dioxide (CO₂). Foam. Dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not allow run-off from fire fighting to enter drains or water courses.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Hydrocarbons.

Reference to Other Sections

Refer to section 9 for flammability properties

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material, then place in suitable container.

Methods for Cleaning Up: Dispose of waste safely and in accordance with local, state, federal, national, and international regulations.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Keep from freezing. Keep containers tightly closed in a cool, well-ventilated place.

Incompatible Materials: None known.



Safety Data Sheet – Gorilla Construction Adhesive

Date Revised:
Date Issued: 3/13/2018

Version: 1.0

FOR CHEMICAL EMERGENCY:
During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific End Use(s)

Construction Adhesive

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Limestone (1317-65-3)		
USA NIOSH	NIOSH (TWA) (mg/m ³)	5 mg/m ³ (respirable dust) 10 mg/m ³ (total dust)
USA OSHA	OSHA PEL (mg/m ³)	5 mg/m ³ (respirable fraction) 15 mg/m ³ (total dust)
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL STEL (mg/m ³)	20 mg/m ³ (total dust)
British Columbia	OEL TWA (mg/m ³)	3 mg/m ³ (respirable fraction) 10 mg/m ³ (total dust)
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline Silica)
Nunavut	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass) 10 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass) 10 mg/m ³ (total mass)
Québec	VEMP (mg/m ³)	10 mg/m ³ (Limestone, containing no Asbestos and <1% Crystalline Silica-total dust)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL TWA (mg/m ³)	30 mppcf
Yukon	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
USA ACGIH	ACGIH chemical category	A2 – Suspected Human Carcinogen
USA OSHA	OSHA PEL TWA (mppcf)	250 mppcf/% SiO ₂ +5 (respirable fraction)
USA OSHA	OSHA PEL TWA (mg/m ³)	10 mg/m ³ /%SiO ₂ +2 (respirable fraction)
USA OSHA	OSHA PEL TWA (mg/m ³)	30 mg/m ³ /%SiO ₂ +2 (total dust)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate)
British Columbia	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable)
Manitoba	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
New Brunswick	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
Nova Scotia	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
Nunavut	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable mass) 0.3 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable mass)



Safety Data Sheet – Gorilla Construction Adhesive

Date Revised:
Date Issued: 3/13/2018

Version: 1.0

FOR CHEMICAL EMERGENCY:
During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

		0.3 mg/m ³ (total mass)
Ontario	OEL Ceiling (mg/m ³)	0.1 mg/m ³ (designated substances regulation-respirable)
Prince Edward Island	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
Québec	VEMP (mg/m ³)	0.1 mg/m ³ (respirable dust)
Saskatchewan	OEL TWA (mg/m ³)	0.05 mg/m ³ (respirable fraction)
Yukon	OEL TWA (mg/m ³)	300 particle/mL
Mexico	OEL TWA (mg/m ³)	0.1 mg/m ³

Exposure Controls

Appropriate Engineering Controls: Use with local exhaust ventilation. Ensure adequate ventilation, especially in confined areas. Use explosion-proof ventilating equipment.

Personal Protective Equipment: Protective clothing. Safety glasses. Gloves.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Wear safety glasses with side shields (or goggles). Avoid contact with eyes.

Skin and Body Protection: Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Paste
Appearance	: Cream
Odor	: Not available
Odor Threshold	: Not available
pH	: 7.5-9
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: 100 °C (212 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: 1.3 - 1.36
Specific gravity	: Not available
Density	: Not available



Safety Data Sheet – Gorilla Construction Adhesive

Date Revised:
Date Issued: 3/13/2018

Version: 1.0

FOR CHEMICAL EMERGENCY:
During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solubility	:	Soluble in water.
Partition Coefficient: N-Octanol/Water	:	Not available
Viscosity	:	Not available
VOC (%)	:	Not available
Solid Content (%)	:	68
Explosion Data – Sensitivity to Mechanical Impact	:	Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	:	Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: None known.
Chemical Stability: Stable under recommended handling and storage conditions (see section 7).
Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Keep from freezing.
Incompatible Materials: None known.
Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Hydrocarbons.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not available
LD50 and LC50 Data: Not available
Skin Corrosion/Irritation: Not available
pH: Not applicable
Serious Eye Damage/Irritation: Not available
pH: Not applicable
Respiratory or Skin Sensitization: Not available
Germ Cell Mutagenicity: Not available
Teratogenicity: Not available
Carcinogenicity: Not available
Specific Target Organ Toxicity (Repeated Exposure): Not available
Reproductive Toxicity: Not available
Specific Target Organ Toxicity (Single Exposure): Not available
Aspiration Hazard: Not available
Symptoms/Injuries After Inhalation: Not available
Symptoms/Injuries After Skin Contact: Not available
Symptoms/Injuries After Eye Contact: Not available
Symptoms/Injuries After Ingestion: Not available
Chronic Symptoms: Not available

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Limestone (1317-65-3)	
Oral LD50 Rat	>5000 mg/kg
Quartz (14808-60-7)	
Oral LD50 Rat	>5000 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

Toxicity Not available
Persistence and Degradability Not available
Bioaccumulative Potential Not available



Safety Data Sheet – Gorilla Construction Adhesive

Date Revised:
Date Issued: 3/13/2018

Version: 1.0

FOR CHEMICAL EMERGENCY:
During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Sewage Disposal Recommendations: Do not dispose of waste into sewer.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT Not regulated for transport

In Accordance with IMDG Not regulated for transport

In Accordance with IATA Not regulated for transport

In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Gorilla Construction Adhesive	
TSCA – Toxic Substance Control Act	The ingredients in this product are listed within this act.

US State Regulations

Gorilla Construction Adhesive	
California Prop 65: This product contains one or more substances listed on Proposition 65 at or above 0.01 wt. %. Quartz (14808-60-7)	

Canadian Regulations

Gorilla Construction Adhesive	
WHMIS Classification	Non-Controlled

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : NEW

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Party Responsible for the Preparation of This Document

The Gorilla Glue Company
+1 513-271-3300

The information presented in this Safety Data Sheet was prepared by qualified personnel and to the best of our knowledge is true and accurate. The information and recommendations are furnished for this product with the understanding that the purchaser will independently determine the suitability of the product for this purpose. This data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which The Gorilla Glue Company assumes legal responsibility. The data is submitted for the user's information and consideration only. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial and local laws and regulations.