

KOOLSEAL

REFLECTIVE ROOF COATINGS



STORM PATCH®
RUBBERIZED LEAK SEALER
KS0065100 WHITE
KS0065125 BLACK
KS0065150 CLEAR

FEATURES & BENEFITS

- Satisfaction Guaranteed
- Leak-free seal
- Prevents moisture penetration and corrosion

PRODUCT DESCRIPTION

Kool Seal® Storm Patch® Rubberized Leak Sealer (KS0065100, KS0065125, KS0065150) provides a flexible, leak-free seal that prevents moisture penetration and corrosion on common building materials and surfaces.

RECOMMENDED USES

- Metal, aluminum, masonry, plastic, asphalt/fiberglass shingles, cedar shake, acrylic roof coatings, cement and shake

ORDERING INFORMATION

Part Number	Color/Size
KS0065100-18	White (12 fl oz Aerosol)
KS0065125-18	Black (12 fl oz Aerosol)
KS0065150-18	Clear (12 fl oz Aerosol)



PRODUCT CHARACTERISTICS

Technology	Alkyd
Color	White, Black, Clear
Finish	Flat
Drying Time	Dries to touch: 10 minutes Can be coated with Kool Seal Elastomeric Coatings in 24 hours

Dry time is temperature, humidity and film thickness dependent

COVERAGE RATES

Up to 15 sq ft

KOOLSEAL

REFLECTIVE ROOF COATINGS



STORM PATCH®
RUBBERIZED LEAK SEALER
KS0065100 WHITE
KS0065125 BLACK
KS0065150 CLEAR

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in U.S.) or contact your local health authority.

Surface must be power washed (minimum 2,000 psi) to remove dirt, and other foreign matter which could prevent proper adhesion. Surfaces must be completely dry prior to coating.

APPLICATION

Spray outdoors or in a well-ventilated area. Protect surrounding areas. Best results when air & surface temperature is between 40°F (4.4°C) and 80°F (26.7°C). For best results, do not use in high humidity.

Shake can for 2 minutes after ball within begins to rattle. Continue to shake for 10 seconds after each minute of use. Test spray in an inconspicuous area for compatibility. Hold can 12"-16" from surface, spray in sweeping motion side to side with a slight overlap. Apply multiple thin coats. For specific application guidelines, call 888-321-KOOL (5665).

After Use: To prevent clogs, hold can upside down & spray until clear gas appears. To clean paint on dial, wear eye protection & wipe off with lacquer thinner. DO NOT stick pin in dial opening. Recycle empty can per local regulations.

CLEANUP

Mineral spirits. Follow manufacturer's instructions for safe use.

CAUTIONS

- Use with adequate ventilation.
- Keep out of the reach of children.
- Use a NIOSH-approved respirator, when necessary.
- Do not take internally.
- In case of ingestion, CALL A PHYSICIAN immediately. DO NOT induce vomiting.
- If splashed in the eyes, flush thoroughly with clean water for a minimum of 15 minutes. CALL A PHYSICIAN immediately. May cause irritation to the skin. If brought into contact with the skin, wash thoroughly with soap and water. Seek medical attention if redness or irritation occurs. Avoid breathing vapors and spray mist. Reseal container after each use. Wear protective clothing, gloves and goggles. Read MSDS before using product.

LIMITED WARRANTY

From date of purchase, if this product fails to perform in accordance with the specifications set forth on this label when applied according to label directions, as your sole and exclusive remedy, upon proof of purchase, we will replace the product at no cost or refund the original purchase price. Labor or costs associated with labor not included. This warranty is made to the original purchaser only and is not transferable. This warranty excludes failure due to improper surface preparation, structural defects, or failure of other previously applied products. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

TECHNICAL SERVICES

1-888-321-KOOL (5665) www.koolseal.com

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of KST Coatings and The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your KST or Sherwin-Williams representative to obtain the most recent Product Data Sheet.