



**FEATURES & BENEFITS**

- Provides a watertight, flexible seal for asphalt surfaces
- Rejuvenates dried out asphalt surfaces
- Protects against the elements, extending the life of the surface and preventing freeze/thaw cracking
- 3 Year Warranty



**PRODUCT DESCRIPTION**

Kool Seal™ Emulsion Driveway Sealer (73-300) is an asphalt-emulsion based driveway sealer that penetrates and rejuvenates dried out asphalt surfaces. It provides a black protective finish, which helps eliminate water penetration and prevent freeze/thaw cracking.

**RECOMMENDED USES**

- Asphalt driveways surfaces
- Do NOT apply to concrete
- Allow new driveways a period of 6 months to cure before sealing

**ORDERING INFORMATION**

Part Number/SMIS	Color/Size
KS0073300-20 / 650848088	Black (5-Gallon)
KS0073300-27 / 650848070	Black (55-Gallon Drum)

**PRODUCT CHARACTERISTICS**

Vehicle	Asphalt
Color	Black
Weight per Gallon	9.09
Weight Solids	26-28%
VOC	< 50 g/L
Drying Time	4 hours for light traffic

*Temperatures below 65°F and relative humidity above 60% will increase the cure time. Avoid parking vehicles on coated surfaces for 24 hours. Dry time is temperature, humidity and film thickness dependent*

**COVERAGE RATES**

Apply at 100 sq.ft.per gallon per coat for smooth or previously sealed driveways. Rough, porous or previously unsealed driveways may require slightly more. Over application will increase cure time and increase the risk of surface defects.

### ***SURFACE PREPARATION***

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in U.S.) or contact your local health authority.

Surface must be power washed (minimum 2,000 psi) to remove dirt, and other foreign matter which could prevent proper adhesion. Oil and grease spots should be scrubbed with driveway cleaner or strong household detergent. Flush the area with clean water and allow to dry before sealing. Repair all cracks larger than 1/8". Cracks smaller than 1/2" may be repaired using Kool Seal Pourable Driveway Crack Filler. Larger cracks should be repaired using Kool Seal Trowel Grade Crack Filler. Allow repaired areas to dry prior to sealing.

### ***APPLICATION***

Best results are achieved when applied at temperatures at or above 65°F in the morning on a clear sunny day. Lightly dampen the surface with water when applied in temperatures above 80°F. Surface may be damp during application but puddles of water should be avoided.

Apply directly into cracks using a putty knife or squeegee. Use firm pressure to ensure all voids are sealed. Finished surface may be smoothed using a putty knife dipped in mineral spirits. For specific application guidelines, call 888-321-KOOL (5665).

### ***CLEANUP***

Soap and water while wet. Mineral spirits when dry.

### ***CAUTIONS***

- Use with adequate ventilation.
- Keep out of the reach of children.
- Use a NIOSH-approved respirator, when necessary.
- Do not take internally.
- In case of ingestion, CALL A PHYSICIAN immediately. DO NOT induce vomiting.
- If splashed in the eyes, flush thoroughly with clean water for a minimum of 15 minutes. CALL A PHYSICIAN immediately. May cause irritation to the skin. If brought into contact with the skin, wash thoroughly with soap and water. Seek medical attention if redness or irritation occurs. Avoid breathing vapors and spray mist. Reseal container after each use. Wear protective clothing, gloves and goggles. Read MSDS before using product.

### ***LIMITED WARRANTY***

For 3 years from date of purchase, if this product fails to perform in accordance with the specifications set forth on this label when applied according to label directions, as your sole and exclusive remedy, upon proof of purchase, we will replace the product at no cost or refund the original purchase price. Labor or costs associated with labor not included. This warranty is made to the original purchaser only and is not transferable. This warranty excludes failure due to improper surface preparation, structural defects, or failure of other previously applied products. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

### ***TECHNICAL SERVICES***

1-888-321-KOOL (5665) [www.koolseal.com](http://www.koolseal.com)

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of KST Coatings and The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your KST or Sherwin-Williams representative to obtain the most recent Product Data Sheet.