



FEATURES & BENEFITS

- Provides a tight, flexible seal for asphalt and concrete surfaces
- Fills cracks up to 1" wide
- Protects against the elements, extending the life of the surface



PRODUCT DESCRIPTION

Kool Seal™ Trowel Grade Crack Filler (75-200) is a fibered sealant designed to fill cracks up to 1" wide in horizontal asphalt or concrete surfaces. Cracks can be filled to blend in with blacktop surfaces and prevent damage caused by water penetration.

RECOMMENDED USES

- Fills cracks in
- Asphalt & concrete joints
 - Driveways & parking areas up to 1" width

ORDERING INFORMATION

Part Number/SMIS	Color/Size
KS0075200-16 / 650848005	Black (1-Gallon)

PRODUCT CHARACTERISTICS

Vehicle	Asphalt
Color	Black
Weight per Gallon	11.5 lb/gal
VOC	< 250 g/L
Drying Time (2-coat application) <i>*Allow 24-48 hours before topcoating with a driveway sealer</i>	24 hours between applications for cracks deeper than 1/2"

COVERAGE RATES

30-40 linear feet for a 1/2" x 1" crack. Coverage rates will vary based on the size of the crack.

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in U.S.) or contact your local health authority.

Broom or hose down the surface to remove dirt, loose dust, debris and other foreign matter which could prevent proper adhesion. Remove any standing water. Oil and grease spots should be scrubbed with driveway cleaner or a strong household detergent. Flush the area with clean water and allow to dry before sealing.

APPLICATION

Best results are achieved when temperature is at least 50°F, and when rain is not likely within 24 hours.

Apply directly into cracks using a putty knife or squeegee. Use firm pressure to ensure all voids are sealed. Finished surface may be smoothed using a putty knife dipped in mineral spirits. For specific application guidelines, call 888-321-KOOL (5665).

CLEANUP

Mineral spirits.

CAUTIONS

- Use with adequate ventilation.
- Keep out of the reach of children.
- Use a NIOSH-approved respirator, when necessary.
- Do not take internally.
- In case of ingestion, CALL A PHYSICIAN immediately. DO NOT induce vomiting.
- If splashed in the eyes, flush thoroughly with clean water for a minimum of 15 minutes. CALL A PHYSICIAN immediately. May cause irritation to the skin. If brought into contact with the skin, wash thoroughly with soap and water. Seek medical attention if redness or irritation occurs. Avoid breathing vapors and spray mist. Reseal container after each use. Wear protective clothing, gloves and goggles. Read MSDS before using product.

LIMITED WARRANTY

From date of purchase, if this product fails to perform in accordance with the specifications set forth on this label when applied according to label directions, as your sole and exclusive remedy, upon proof of purchase, we will replace the product at no cost or refund the original purchase price. Labor or costs associated with labor not included. This warranty is made to the original purchaser only and is not transferable. This warranty excludes failure due to improper surface preparation, structural defects, or failure of other previously applied products. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

TECHNICAL SERVICES

1-888-321-KOOL (5665) www.koolseal.com

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of KST Coatings and The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your KST or Sherwin-Williams representative to obtain the most recent Product Data Sheet.